

Boat Manufactured By:

## SEA PRO

25214 Hwy 121 • Whitmire, SC 29178

(803) 694-2644

<https://seapromfg.com/>

### SEA PRO 292 OFFSHORE

|                            |           |
|----------------------------|-----------|
| Length                     | 28' 6"    |
| Beam                       | 9' 10"    |
| Dry Weight (Boat Mfr. Pub) | 6,800 lbs |
| Maximum HP                 | 700 hp    |
| Fuel Capacity              | 175 gal   |
| Weight as Tested           | 9,107 lbs |

### F300XSB / LF300XSB

|                    |               |
|--------------------|---------------|
| Horsepower         | 300 hp        |
| Induction          | EFI/VCT/DOHC  |
| Displacement       | 4.2L          |
| Weight (Estimated) | 611 - 611 lbs |
| Gear Ratio         | 1.75:1        |

### ENGINE MOUNTING HEIGHT

|                          |                      |
|--------------------------|----------------------|
| Mounting Hole Position   | #1                   |
| Ventilation Plate Height | 1" Above Boat Bottom |

### PROPELLER(S)

|                    |                                   |
|--------------------|-----------------------------------|
| Series             | Saltwater Series II               |
| Diameter x Pitch   | 15-1/4 x 19                       |
| Yamaha Part #      | 6CF-45970-20-00 / 6CE-45970-20-00 |
| Propeller Material | Stainless Steel                   |

### TEST CONDITIONS

|                                      |               |
|--------------------------------------|---------------|
| Number of People                     | 3             |
| Air / Water Temperature (Fahrenheit) | 77° F / 69° F |
| Elevation (in feet above sea level)  | 200'          |
| Wind Velocity                        | 5-10 MPH      |

### COMMENTS

Test weight includes 50 gallons of fuel, 4 batteries, safety and test equipment.

YPB#: PB\_SEP\_292 O shore\_TW\_F300XSB\_5-2-2024\_OCC



**Engine:** Yamaha F300XSB / LF300XSB

**Boat:** Sea Pro 292 O shore

**Configuration:** Twin

**Test Date:** 2-May-2024



### PERFORMANCE DATA

| RPM                         | MPH         | GPH         | MPG         |
|-----------------------------|-------------|-------------|-------------|
| 1000                        | 6.1         | 2.7         | 2.26        |
| 1500                        | 8.4         | 4.3         | 1.95        |
| 2000                        | 10.6        | 7.1         | 1.49        |
| 2500                        | 17.6        | 9.9         | 1.78        |
| <b>3000</b>                 | <b>26.1</b> | <b>11.9</b> | <b>2.19</b> |
|                             |             | 15.1        |             |
| 3500                        | 32.4        | 20.8        | 2.15        |
| 4000                        | 38.4        | 26.5        | 1.85        |
| 4500                        | 43.2        | 32.8        | 1.63        |
| 5000                        | 48.0        | 40.9        | 1.46        |
| 5500                        | 52.3        | <b>51.8</b> | 1.28        |
| <b>5950</b>                 | <b>57.5</b> |             | <b>1.11</b> |
| Time to Plane: 3.87 seconds |             |             |             |
| 0-30 MPH: 6.43 seconds      |             |             |             |

**NOTICE TO CONSUMER** The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not

be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed